

FLECK Flex exhaust gas universal feedthrough (variable)

For DN 100 and DN 125



Download Product Information
fleck-dach.de/downloads

Product Description

The FLECK Flex exhaust gas universal feedthrough (variable) provides a universal and environmentally friendly solution for connecting flue systems on pitched roofs.

Thanks to the flexible flashing made of ECO FORM, our sustainable alternative to conventional lead sheet, this roof penetration can be used independently of the roof tile model. The product is available for pipe diameters DN 100 and DN 125.

Due to the excellent material properties of ECO FORM and the generously dimensioned flashing, the roof feedthrough can be easily adapted to the surrounding roof tiles and integrated into almost any roof surface. The connection remains watertight even under extreme weather conditions.

The adjustable black EPDM insert allows convenient alignment of the pipe passing through the penetration.

Available in the standard colors black, red, and brown, this roof feedthrough integrates harmoniously into any roof appearance.

- Flashing dimension: 570 (L) x 500 (B) mm
- Available in black, red and brown

Applications

- Flexible universal roof feedthrough for flue gas pipes (e.g. heating systems) and other pipes on pitched roofs

Material

- Base element made of weather-resistant, durable rigid PVC
- Flexible lead-replacement flashing made of ECO FORM
- Penetration insert made of EPDM (black)

Fire Classification

- B2 according to DIN 4102-4



Download Installation Manual
fleck-dach.de/downloads