



FLECK Gravel traps for flat roof drains

Universal gravel trap DN 70–DN 150



Gravel trap/Screen DN 50



Parapet-universal gravel trap DN 70–DN 125



PRODUCT INFORMATION

The universal gravel trap, with its flow-optimised dome grating design, is fitted above the flat roof gully or drain to protect the drainage pipe from blockages and to improve the drainage capacities. It should be cleaned and any deposits removed as part of the regular maintenance to ensure its full functionality.

Material

All components are made of highly weather-resistant, durable, black coloured PP.

Construction material class


B2

Notes on universal gravel trap


- The universal gravel trap dome grating for the surface can be loaded up to 100 kg and cannot be driven over
- The three push-fit feet made of stable, fibre reinforced plastic allow variable use for drains from DN 70–DN 150 with the universal gravel trap and from DN 70–DN 125 with the parapet universal gravel trap.
- The feet are simply inserted into the respective plug-in devices for DN 70, DN 100, DN 125, DN 150 (reversible connection) and automatically tighten in the drain
- Maintenance of the drains is always possible by manual removal of the universal gravel trap (without dismantling tools) even when water is backed up

TECHNICAL NOTES

Flat roof screen and gravel trap DN 50



Universal-gravel trap and parapet-universal-gravel trap DN 70–DN 150



Nominal diameter	Dimensions (mm)			
	A	B	C	D
DN 50	50	23	115	20
DN 70–DN 150*	210	80	135	–

Dimensions in mm

* Note: Adaptation to the nominal width using the plug-in feet (length x = 55 mm)