



FLECK

Dachzubehör!



Made from
recycled raw
material!

The lead substitute for the roof

FLECK ECO FORM – The sustainable material for precise seaming work on the valley, ridge, fireplace, dormer, etc.

The ECO FORM product range is an innovative substitute for rolled lead. Its production is very environmentally friendly. It is also safe to use. ECO FORM products are lightweight, easy to apply and are particularly suitable for sealing flashings on roofs, for example, in the following areas:

- Chimneys
- Dormers
- Roof windows/In-roof solar panels
- Barge boards
- Walls and other roof structures



Now find out more about
FLECK ECO FORM:
fleck-dach.de/en/eco-form-en

made by **Leadax**



The material is so mouldable that even roofing details can be highlighted.

The sustainable alternative to traditional rolled lead

With **ECO FORM EASY**, **ECO FORM MAX** and **ECO FORM BASIC**, ECK offers roofers a high-quality and environmentally friendly alternative to rolled lead.

Three products – plenty of advantages:

- Easier to use and transport, as up to 75 % lighter than rolled lead
- Very high extensibility – without cracking
- Easy to cut with stable snips
- East to mould and install
- Very good compatibility with metals and roofing materials
- UV-stable and very durable



1 Measure



2 Cut



3 Preform



4 Finalise in detail

Easy to use

The products are installed in different ways:

- **ECO FORM EASY** is attached using the two self-adhesive strips on the back
- **ECO FORM MAX**, on the other hand, is completely coated with butyl adhesive on the back
- **ECO FORM BASIC** is delivered without adhesive on the back; it can be fixed instead with the help of our Leadax HIGH-TACK sealant
- The material can be moulded by hand or with the help of a dresser or roller.



Brick red*

Lead grey

Black

DIMENSIONS (W x L in mm)	ECO FORM EASY	ECO FORM MAX	ECO FORM BASIC
330 x 5,000	✓	✓	✗
500 x 5,000	✗	✓	✗
500 x 6,000	✗	✗	✓

*Does not apply to ECO FORM BASIC



Sustainably produced

The FLECK ECO FORM products are made from recycled polyvinyl butyral (PVB), which is obtained from automotive laminated glass interlayer films in a recycling method. The expanded metal used is aluminium. At the end of their life, ECO FORM products are almost completely recyclable.



Quality tested by Kiwa

FLECK ECO FORM products have been tested for durability and watertightness by the Dutch test institute Kiwa. The result: ECO FORM products have convincingly high ageing and long-term resistance. The watertightness with a water column of 10,000 mm was tested and confirmed for at least 25 years.



ZVDH certified



All FLECK ECO FORM products meet the strict "Green Building" criteria of the ZVDH. The ZVDH bases its criteria on the German "Sustainable building rating system of the Federal Government" (BNB) as well as the state "Sustainable building quality seal" (QNG).