

FLECK Flex exhaust gas universal feedthrough (variable)

For DN 100 and DN 125



Download Product Information
fleck-dach.de/downloads



Product Description

The FLECK Flex exhaust gas universal feedthrough (variable) provides a universal solution for connecting flue systems on pitched roofs.

Thanks to the flexible flashing made of ECO FORM, our alternative to conventional lead sheet, this roof penetration can be used independently of the roof tile model. The product is available for pipe diameters DN 100 and DN 125.

Due to the material properties of ECO FORM and the generously dimensioned flashing, the roof feedthrough can be easily adapted to the surrounding roof tiles and integrated into almost any roof surface. Even under severe weather conditions, the design ensures a permanently tight seal.

The adjustable black insert allows convenient alignment of the pipe passing through the penetration.

Available in the standard colors black, red, and brown, this roof feedthrough integrates harmoniously into any roof appearance.

- Flashing dimension: 570 (L) x 500 (B) mm
- Available in black, red and brown

Applications

- Flexible universal roof feedthrough for flue gas pipes (e.g. heating systems) and other pipes on pitched roofs with a maximum pitch of 45°

Material

- Base element made of rigid PVC
- Flexible lead-replacement flashing made of ECO FORM (PVB-based rolled lead substitute with aluminum expanded metal)
- Penetration insert made of plasticized PVC (black)

Fire Classification

- B2 according to DIN 4102-4

Technical Notes

- The product functions properly only if installed correctly and professionally. Please refer to the installation instructions for FLECK universal products (scan the QR code).



Download Installation Manual
fleck-dach.de/downloads